

**In the Claims:**

Please amend claims 4 and 15 as follows (the changes in these claims are shown with ~~striketrough~~ for deleted matter and underlines for added matter). A complete listing of the claims is listed below with proper claim identifiers.

1. (Previously Presented) A variable rate multi-arc leaf spring assembly comprising:

a main leaf spring constructed of a composite material, said leaf spring defining an upwardly curved central arc portion having a first radius and at least one pair of upwardly curved peripheral arc portions extending from said central arc portion and having radii not equal to said first radius,

wherein said main leaf spring provides a continuous variable spring deformation rate including a soft spring rate and a hard spring rate.

2. (Original) The variable rate multi-arc leaf spring assembly of claim 1 wherein said composite material consists of a fiber-reinforced resin.

3. (Original) The variable rate multi-arc leaf spring assembly of claim 1 wherein said main leaf spring further defines a uniform cross-sectional area throughout the length.

4. (Currently Amended) The variable rate multi-arc leaf spring assembly of claim 1 wherein said main leaf spring further includes at least one integral mounting end connected with at least one upwardly curved peripheral arc portion of said at least one pair of upwardly curved peripheral arc portions, said at least one integral mounting end adapted to be connected to a loading structure.

5. (Original) The variable rate multi-arc leaf spring assembly of claim 4 wherein said at least one integral mounting end comprising a mounting eyelet.

6. (Previously Presented) The variable rate multi-arc leaf spring assembly of claim 5 wherein said mounting eyelet includes an out-of-mold metallic insert for installation.

7. (Previously Presented) The variable rate multi-arc leaf spring assembly of claim 1 further comprising a load plate mounted beneath said main leaf spring, wherein said load plate gradually engages said main leaf spring during a predetermined set of payload conditions to enhance said soft spring rate.

8. (Previously Presented) The variable rate multi-arc leaf spring assembly of claim 7 wherein said load plate is constructed of said composite material.

9. (Original) The variable rate multi-arc leaf spring assembly of claim 7 wherein said load plate defines a uniform cross-sectional area throughout its length.

10. (Original) The variable rate multi-arc leaf spring assembly of claim 7 further comprising an intermediary member spaced between said leaf spring and said load plate.

11. (Original) The variable rate multi-arc leaf spring assembly of claim 10 wherein said intermediary member is constructed of urethane.

12. (Previously Presented) A variable rate multi-arc leaf spring assembly comprising:

a main leaf spring constructed of a composite material, said main leaf spring defining an upwardly curved central arc portion having a first radius and at least one pair of upwardly curved peripheral arc portions extending from said central arc portion and having radii not equal to said first radius, wherein said main leaf spring provides a continuous variable spring deformation rate including a soft spring rate and a hard spring rate; and

a load plate mounted beneath said main leaf spring, wherein said load plate gradually engages said main leaf spring during a predetermined set of payload conditions to enhance said soft spring rate.

13. (Original) The variable rate multi-arc leaf spring assembly of claim 12 wherein said composite material consists of a fiber-reinforced resin.

14. (Original) The variable rate multi-arc leaf spring assembly of claim 12 wherein said main leaf spring defines a uniform cross-sectional area throughout its length.

15. (Currently Amended) The variable rate multi-arc leaf spring assembly of claim 12 wherein said mail leaf spring further includes at least one integral mounting end connected with at least one upwardly curved peripheral arc portion of said at least one pair of upwardly curved peripheral arc portion, said at least one integral mounting end adapted to be connected to a loading structure.

16. (Original) The variable rate multi-arc leaf spring assembly of claim 15 wherein said at least one integral mounting end comprises a mounting eyelet.

17. (Previously Presented) The variable rate multi-arc leaf spring assembly of claim 16 wherein said mounting eyelet includes an out-of-mold metallic insert for installation.

18. (Previously Presented) The variable rate multi-arc leaf spring assembly of claim 12 wherein said load plate is constructed of said composite material.

19. (Original) The variable rate multi-arc leaf spring assembly of claim 12 wherein said load plate defines a uniform cross-sectional area throughout its length.

20. (Original) The variable rate multi-arch leaf spring assembly of claim 12 further comprising an intermediary member spaced between said leaf spring and said load plate.

21. (Original) The variable rate multi-arc leaf spring assembly of claim 20 wherein said intermediary member is constructed of urethane.

22. (Canceled)

23. (Canceled)

24. (Canceled)

25. (Canceled)

26. (Canceled)

27. (Canceled)

28. (Canceled)

29. (Canceled)

30. (Canceled)

31. (Previously Presented) A method of achieving a continuous non-linear variable spring deformation rate for a multi-arc leaf spring assembly comprising:

providing a main leaf spring defining a central arc portion having a first radius and at least one pair of upwardly curved peripheral arc portions having radii not equal to said first radius;

providing a load plate beneath said main leaf spring;

applying a downward force to said main leaf spring, wherein said central arc portion of said main leaf spring flexes and gradually engages said load plate to achieve an enhanced soft spring rate; and

applying an increased downward force to said main leaf spring, wherein said central arc portion engages said load plate throughout a length of said load plate and said at least one pair on peripheral arc portions flexes to achieve a hard spring rate with a continuous transition from said soft spring rate to said hard spring rate.

32. (Previously Presented) The method of claim 31 wherein said main leaf spring further includes at least one integral mounting end connected with said at least one peripheral arc portion, said at least one mounting end adapted to be connected to a loading structure.

33. (Previously Presented) The method of claim 31 further comprising the method of separating said main leaf spring from said load plate under empty payload conditions with an intermediary member.